

The powerful Van tyre.

EUROVAN



Built to meet the toughest demands of powerful US vehicles, optimised to European road conditions through a combination of flat belt technology and tread design, the Eurovan ensures high mileage performance, real security and powerful traction!

Vehicle Examples

CITROEN	OPEL
FIAT	PEUGEOT
FORD	RENAULT
MERCEDES	TOYOTA
NISSAN	VOLKSWAGEN



EUROVAN - The guarantee for top performance

The tread pattern is characterised by a combination of two centre siped tread bands with wide shoulder blocks and three broad drainage channels that give the tyre its top performance and impressive rigidity.



Three drainage channels

Wide shoulder block

Multiple tread sipes

Center tread bands

Features

- 1 Three drainage channels
- 2 Multiple tread sipes
- 3 Wide shoulder blocks
- 4 Centre tread bands
- 5 Wide flat belt tread profile ensuring flat and wider contact patch
- 6 Steel belted casing with high impact resistance

Benefits

- 1 Excellent water dispersion from the contact patch ensuring top wet performance
- 2 Low noise levels and break up of water surface tension.
- 3 Improved handling under load
- 4 Better steering and stability
- 5 Smoother, more comfortable ride and higher mileage
- 6 Greater rigidity and strength

PATTERN	RIM DIA-METER	SIZE	PR	SERVICE DESCRIPTION ¹⁾	RIMS	TL VALVE (TUBE AND VALVE)	LOAD INDEX	WHEEL POSITION ²⁾	LOAD CAPACITY (KG) PER AXLE AT TIRE PRESSURE (BAR)								SPEED INDEX AND REFERENCE SPEED (KM/H)
									3.0	3.25	3.5	3.75	4.0	4.25	4.5	4.75	
EUROVAN	14"	185R14 C	8	102/100 Q	5 J 51/2 J (1440, 6 J 38 G 11.5)	43 GS 11.5	102 100	S T	1230 2315	1310 2465	1390 2620	1470 2765	1545 2915	1625 3060	1700 3200	Q 160	
		195R14 C	8	106/104 Q	5 J 51/2 J (1460, 6 J 38 G 11.5)	43 GS 11.5	106 104	S T	1375 2605	1465 2775	1555 2945	1645 3110	1730 3275	1815 3440	1900 3600	Q 160	
	15"	195/70R15 C	8	104/102R	5 J 51/2 J (1540, 6 J 38 G 11.5)	-	104 102	S T	1300 2460	1385 2620	1470 2780	1555 2940	1640 3095	1720 3250	1800 3400	R 170	
		225/70R15 C	8	112/110 R	6 J 61/2 J (1560, 7 J 38 G 11.5)	43 GS 11.5	112 110	S T	1620 3065	1725 3270	1830 3470	1935 3665	2040 3860	2140 4050	2240 4240	R 170	
	16"	175/75R16 C	8	101/99 R	41/2 J 5 J 51/2 J	43 GS 11.5	101 99	S T	1140 2145	1215 2290	1290 2430	1360 2565	1435 2700	1505 2835	1575 2970	1650 3100	R 170
		195/75R16 C	8	107/105 R	5 J 51/2 J 6 J	43 GS 11.5	107 105	S T	1350 2560	1440 2730	1525 2900	1615 3060	1700 3225	1785 3385	1865 3545	1950 3700	R 170

1) Load Index single/twin fitment and Speed Index; 2) S=Single/T=Twin

