

Simex Bias tyres: inflated dimensions and load/speed ratings

M/P Trekker	Load/Speed	Permitted Rim	Sect width mm/inch	Overall Dia mm/inch
7.50-16" 8PR	113/112L	5.0-6.5"	220.9mm / 8.7"	817.1mm / 32.2"

Jungle Trekker 2	Load/Speed	Permitted Rim	Sect width mm/inch	Overall Dia mm/inch
31x9.5-16" 6PR	107Q	6.5-8.5"	253mm / 9.7"	791mm / 31.2"
33x10.5-15" 6PR	115Q	7.0-9.0"	291mm / 11.5"	857mm / 33.7"
33x10.5-16" 6PR	114Q	7.0-9.0"	291mm / 11.5"	857mm / 33.7"
33x11.5-15" 6PR	117Q	8.0-10.0"	305mm / 12.0"	864mm / 34.0"
33x11.5-16" 6PR	116Q	8.0-10.0"	295mm / 11.6"	864mm / 34.0"
34x10.5-15" 6PR	114Q	7.0-9.0"	282mm / 11.1"	871mm / 34.3"
34x10.5-16" 6PR	113Q	7.0-9.0"	282mm / 11.1"	871mm / 34.3"
34x11.5-15" 6PR	119Q	8.0-10.0"	292mm / 11.5"	879mm / 34.6"
34x11.5-16" 6PR	118Q	8.0-10.0"	292mm / 11.5"	879mm / 34.6"

Extreme Trekker

The Centipede

	Load/Speed	Permitted Rim	Sect width mm/inch	Overall Dia mm/inch
29x7.5-15" 6PR	99N	5.0-6.5"	202mm / 7.95"	732mm / 28.8"
31x10.5-15" 6PR	110N	7.0-9.0"	266mm / 10.5"	818mm / 32.2"
32x9.5-15" 6PR	111N	6.5-8.5"	268mm / 10.5"	849mm / 33.4"
32x9.5-16" 6PR	110N	6.5-8.5"	268mm / 10.5"	849mm / 33.4"
32x10.5-15" 6PR	113N	7.0-9.0"	281mm / 11.1"	847mm / 33.3"
32x10.5-16" 6PR	111N	7.0-9.0"	281mm / 11.1"	847mm / 33.3"
35x10.5-15" 6PR	120L	7.0-9.0"	305mm / 12.0"	887mm / 34.9"
35x10.5-16" 6PR	119L	7.0-9.0"	305mm / 12.0"	887mm / 34.9"

Extreme Trekker 2

The Centipede

	Load/Speed	Permitted Rim	Sect width mm/inch	Overall Dia mm/inch
35x11.5-15" 6PR	121N	8.0-10.0"	320mm / 12.6"	901mm / 35.5"
35x11.5-16" 6PR	120N	8.0-10.0"	320mm / 12.6"	901mm / 35.5"
36x12.5-15" 6PR	124N	8.5-11.0"	340mm / 13.4"	920mm / 36.2"
36x12.5-16" 6PR	123N	8.5-11.0"	340mm / 13.4"	920mm / 36.2"