

Get into the **G**World

**The on-road and  
light off-road specialists.**

Grabber New Generation

# GRABBER HP/UHP



Developed for fast and powerful SUV/4X4, the stars of the Grabber family are high achievers, providing safe driving on asphalt roads as well as in light off-road conditions. With their advanced tread patterns, top quality constructions, their wide size range of 15"-24" rim diameters and speed capabilities up to 270 km/h (168 mph), the Grabber HP/UHP don't just look good; they offer top performance in their segment!

## Vehicle Examples

BMW	LAND ROVER
CHRYSLER	MERCEDES
FORD	TOYOTA
KIA	VOLKSWAGEN



**GENERAL TIRE** 

# GRABBER HP/UHP - The guarantee for safe performance

The new tread patterns are characterised by steep, extended grooves from shoulder to centre and siped sturdy tread lugs. The design, in combination with advanced silica tread compounds, and a reinforced construction, make the HP/UHP tyres comfortable, durable and extremely safe in both wet and dry conditions.



## Features

- 1 Steep, extended grooves from centre to shoulder
- 2 Shoulder blocks with multiple edges and additional sipes
- 3 Shallow slots, varying groove angles and increased pattern depth in the shoulder area
- 4 Optimised tyre contour with focus on flat belt and reinforced construction
- 5 High performance silica tread compound

## Benefits

- 1 Very good water displacement; reduces the risk of aquaplaning
- 2 Grip + braking optimisation and smooth rolling; excellent handling and comfort and noise improvement
- 3 Even wear pattern and increased grip edges on soft surfaces like grass or sand; good performance also in light off-road conditions
- 4 Excellent mileage performance and comfort improvement for higher speed (speed symbols up to V and W)
- 5 High grip, for excellent handling, braking and traction in dry and wet

PATTERN	RIM DIA-METER	SIZE	SPEED/LOAD INDEX	LOAD RANGE	SIDE-WALL	RIM PROTECTION	PERMITTED RIMS WIDTH (INCH)		TYRE DIMENSIONS		TREAD PATTERN DEPTH (MM)	ROLLING CIRCUM-FERENCE 1,5%-2,5% (MM)	
							MIN.	MAX.	MAX. IN SERVICE OUTER-Ø (MM)	ON MEASURING RIM WIDTH (MM)			
HP	15"	225/70 R 15	100 T		OWL		6.0	7.5	709	237	8.9	2126	
		235/70 R 15	103 T		OWL		6.0	8.0	725	250	8.9	2169	
		255/70 R 15	108 T		OWL		6.5	8.5	753	270	8.7	2254	
		235/60 R 15	98 T		OWL	FR	6.5	8.5	675	250	8.5	2022	
		255/60 R 15	102 H		OWL	FR	7.0	9.0	699	270	8.7	2095	
UHP	15"	275/60 R 15	107 T		OWL	FR	7.5	9.5	725	290	8.5	2169	
		205/70 R 15	96 H		BSW		5.0	7.0	681	217	8.7	2040	
	16"	265/70 R 15	112 H		BSW		7.0	9.0	767	282	8.7	2297	
		215/70 R 16	100 H		BSW		5.5	7.0	720	230	8.9	2159	
		225/70 R 16	102 H		BSW		6.0	7.5	734	237	8.9	2202	
		235/70 R 16	106 H		BSW		6.0	8.0	750	250	8.9	2245	
		245/70 R 16	107 H		BSW		6.5	8.0	764	258	8.7	2288	
		265/70 R 16	112 H		BSW		7.0	9.0	792	283	8.7	2373	
		275/70 R 16	114 T		BSW	FR	7.0	9.0	808	290	8.7	2416	
	17"	215/65 R 16	98 H		BSW		6.0	7.5	698	230	8.9	2092	
		255/65 R 16	109 H		BSW		7.0	9.0	752	270	8.9	2251	
		235/60 R 16	100 H		BSW		6.5	8.5	700	250	8.5	2098	
		255/55 R 16	103 T		BSW	FR	7.0	9.0	698	276	8.5	2092	
		235/65 R 17	108 V	XL	BSW	FR	6.5	8.5	750	250	8.7	2251	
		255/60 R 17	106 V		BSW	FR	7.0	9.0	750	270	8.9	2251	
		255/55 R 17	97 V		BSW	FR	6.0	8.0	690	242	8.5	2075	
		275/55 R 17	109 V		BSW	FR	7.5	9.5	746	295	8.5	2239	
		255/50 R 17	101 V		BSW	FR	7.0	9.0	698	276	8.5	2098	
		18"	255/55 R 18	109 W	XL	BSW	FR	7.0	9.0	749	276	8.5	2248
	19"		255/50 R 19	107 W	XL	BSW	FR	7.0	9.0	749	276	8.5	2260
			285/45 R 19	111 W	XL	BSW	FR	9.0	10.5	749	296	8.3	2255
	20"	275/55 R 20	117 V	XL	BSW	FR	7.5	9.5	822	295	8.5	2471	
		285/50 R 20	112 V		BSW	FR	8.0	10.0	806	309	8.5	2422	
295/50 R 20		118 V	XL	BSW	FR	8.0	10.5	816	321	8.5	2452		
305/50 R 20		120 V		BSW	FR	8.5	11.0	826	329	8.5	2485		
275/45 R 20		110 V	XL	BSW	FR	8.5	10.5	766	284	8.5	2306		
22"	295/45 R 20	114 V	XL	BSW	FR	9.5	11.0	784	308	8.5	2361		
	295/45 R 22	116 V	XL	BSW	FR	9.5	11.0	835	308	8.5	2516		
	305/45 R 22	118 V	XL	BSW	FR	9.5	11.0	843	315	8.5	2541		
	295/40 R 22	112 V	XL	BSW	FR	10.0	11.5	805	313	8.5	2425		
	305/40 R 22	114 V	XL	BSW	FR	10.0	12.0	813	326	8.5	2450		
23"	305/40 R 23	115 V	XL	BSW	FR	10.0	12.0	838	326	8.5	2525		
	24"	305/40 R 24	117 V	XL	BSW	FR	10.0	12.0	864	326	8.5	2605	
		315/35 R 24	114 V	XL	BSW	FR	10.5	12.5	383	338	8.5	2532	